

DATA LOGGER

hopeDongle G02-WiFi



TIER 1
BloombergNEF

Hopewind is ranked as
Tier 1 Solar Inverter Maker by BNEF

FEATURES



Easy to Use

- Plug and play, quick installation
- Supports cloud platform monitoring services
- Supports remote modify local parameters
- Supports remote firmware upgrade



Flexible

- Supports multiple data formats
- Supports fast adaptation of all kinds of equipment



Stable

- Industrial components and designs, wide temperature range
- Password and encrypted transmission for data protection
- Real-time detection of online status

PARAMETERS

| Model | | hopeDongle-G02-WiFi |
|--------------------------------|--|---------------------|
| External Interface | | |
| Docking Method | USB | |
| Operating Button | RESET | |
| Operating Indicator | LED indicator | |
| General Parameters | | |
| Dimensions (W × H × D) | 118 × 49 × 33.5 mm | |
| Weight | 70 g | |
| Ingress Protection | IP66 | |
| Rated Voltage | DC5~15 V | |
| Max. Current | 125 mA (DC12V) | |
| Operating Temperature | -30~+65°C | |
| Storage Temperature | -40~+85°C | |
| Hardware Parameters | | |
| Data Input Mode | RS485 (9600bps) | |
| Data Output Mode | Wi-Fi | |
| Wi-Fi Parameters | | |
| Operating Frequency | 2.412~2.472GHz | |
| Wireless Standard | 802.11 b/g/n | |
| Data Transmission Rate | 11Mbps@11b, 54Mbps@11g | |
| Operating Mode | AP + STA (coexistence mode) | |
| Software Parameters | | |
| Supported Device Protocols | Modbus-RTU | |
| Software Watchdog | Support | |
| Data Upload Cycles | 5 minutes (default) | |
| Parameter Configuration Method | Hopewind cloud APP | |
| Cloud Platform | Hopewind cloud | |
| Others | | |
| Certification | CE (IEC-60529, IEC-62311, IEC-62368, EMC), EN (300328, 55032), RED | |

