

HOPEWIND

SMART CONTROLLER

hopeComBox 2000-G04



PRELIMINARY

FEATURES



Safe and Reliable

- Supports encrypted transmission of device data and fault protection
- Supports continuous 24/7 insulation impedance detection for enhanced safety
- Requires no negative grounding, resulting in higher system reliability
- IP66 & C5 anti-corrosive design for harsh environment



Intelligent and Flexibly

- Supports dual-winding and dual-split transformer applications
- Supports RS485, PLC, Ethernet, and fiber optic multiple communication interfaces
- Supports multiple types of devices access: smart meter, substation monitoring units, environment sensors, etc.
- Supports IEC 104, Modbus-TCP/RTU, GOOSE, MMS and other communication protocols



Convenient O&M

- Modular design, strong maintainability
- Automatically searches and assigns inverter address for easy commissioning
- Supports batch parameters configuration and firmware upgrades for inverters



Outstanding Performance

- Active PID protection, real-time suppression of PID effect, compatible with P-type/N-type modules
- Adopts Linux embedded operating system, supports WebUI operation
- Adopts dual-core processor, 512MB DDR memory for stable and reliable system performance
- Supports grid dispatch functions (AGC, AVC, fast-frequency response) with extremely rapid response times



PARAMETERS

Model	hopeComBox2000-G04
Devices Regulation	
Max. Number of Inverter Connection	40
Communication Methods	RS485 / RJ45 / PLC / SFP
Fiber Switch	2 optical, 3 electrical
Fiber Optic Terminal Box (Single Mode)	4 inlets, 24 outlets
Communication Ports	
RS485 Ports	COM × 8
Ethernet Ports ^①	ETH × 4
Fiber Optic Ports	SFP × 2
PLC Channel	2
Power Supply	
Rated Input Voltage	220~230 V AC
Rated Frequency	50 Hz / 60 Hz
Max. Input Current	1.5 A
PLC Parameters/Specifications	
Rated Input Voltage	800 V AC
Max. Communication Distance	1000 m
Max. Number of Devices Per Channel	20
PID Parameters	
Rated Input Voltage	800 V AC
Input Voltage Range	640~920 V AC
Max. Input Current	1.2 A
Grid Type	IT
Single PID Max. Output Power	450 W
Max. Output Current	0.6 A
Display	LED
System ISO Detection Accuracy	
2.5~20 K	±10%@25°C
20~50 K	±20%@25°C
General Parameters	
Dimensions (W × H × D)	770 × 750 × 325 mm
Weight	≤ 50 kg
Operating Temperature	-40~+60°C
Operating Humidity	4~100%
Operating Altitude	≤4500 m
Ingress Protection	IP66
Anti-corrosion	C5
Installation Methods	Wall-mounted, pole-mounted
Inlet and Outlet Wires	Bottom in and out
O&M Methods	Front operation and front maintenance

① One of the ethernet ports is exclusively for local debugging.

Note: The parameters depicted in the hopeComBox2000-G04 datasheet are preliminary version and shall not serve as a binding reference for product performance compliance. The final product specifications shall prevail per the actual shipped products.



Shenzhen Hopewind Electric Co., Ltd. All rights reserved. Information may be subject to change without notice.

PRELIMINARY